

Product Function

Measurement of AC leakage current, AC current.

Product features

1. The iron core is made with high performance material and digital integration technology, small volume, high accuracy.
2. Adopts magnetic shielding technology, almost unaffected by the external magnetic field, strong anti-interference ability.
3. Peak hold function. Data storage function.

**Technical Specification**

Power Supply	DC3V Alkaline dry battery LR03 X 2PCS
Range	0.000mA~60.0A
Resolution	1uA
Measurement Accuracy	±1.5%rdg±5dgt (23°C±3°C, below 70%RH)
Meter Weight	0.32kg (include accessories)
Meter Dimension	172mmX71mmX32mm
CT Size	25X30mm
LCD Size	35mmX21.5mm; display area: 32mmX15mm
Sampling Rate	2 times/second
Frequency	50Hz, 60Hz Automatic identification
Data Store	99 groups , flash display "FULL" symbol indicate stored full
Peak Hold	Peak capture and hold function, long press HOLD key display peak value
Data Hold	Data hold function: "DH" symbol display
Overflow Display	Exceed measure range overflow function: "OL" symbol display
Automatic Shut Down	5 Minutes after power on, will shut down automatically without any operation to reduce the power consumption.
Battery Voltage	When battery voltage lower than 2.8V, will display low battery voltage symbol "⚡", remind to replace battery
Working Current	5mA
Line Voltage	Below AC 600V circuit measurement
Shift	Automatically
Accessories	Meter: 1PCS; Tool bag: 1PCS; LR03 Alkaline battery : 2PCS